

Features

- Integrated LED recessed spotlight, 2-axis adjustable (horizontal rotation 360°, vertical tilt 30°), white bezel colour, 3 CCT options of 2700-3000-4000k, lumen up to 550lm, 5.4W, dimmable trailing/leading edge, 38° degree beam angle, aluminium and steel body, low profile 37mm recessed depth, IP65 frontal degree, IK03, loop-in/loop-out terminals for fast wiring, 68mm cutout, clear lens. Air-proof, to limit air leakage when used in residential applications within the building's thermal envelope. Directly coverable with insulation material according to EN60598-1

Product Overview

Product name	OBICO 68 IP65 550lm 3CCT DIM ADJ WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
E-number FI	4278505
Fixture luminous flux (lm)	550
Luminaire efficacy (lm/W)	102
Light colour	Cool White
CRI (Ra)	90
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1
Total power consumption (W)	5.4
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK07

OBICO 68 IP65 550lm 3CCT DIM ADJ WHITE 0005363


Product EAN number

5410288053639

Warranty

5 years

Photometry



Technical drawings

