

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K ALU EM
2023577




PRODUCT OVERVIEW


Product name	OPTIX RECESSED 600x600 2L 4000K ALU EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3600
Luminaire efficacy (lm/W)	138
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	26
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768235773

PHOTOMETRY

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K ALU EM
2023577



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.51	112.8°	122
1.0	3.01	56.4°	31
1.5	4.52	37.6°	14
2.0	6.02	28.2°	8
2.5	7.53	22.5°	5
3.0	9.03	18.5°	3



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.77	75.4°	880
1.0	1.55	37.7°	216
1.5	2.32	25.1°	91
2.0	3.09	18.9°	54
2.5	3.86	15.1°	34
3.0	4.64	12.7°	24

TECHNICAL DRAWINGS

