



### Features

- Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 4000K, CRI80, Non-dimmable, 30800lm, 198W, 156lm/W, Symmetrical Wide beam, 100.000hrs L70B50 lifespan, 450 x 335 x 75mm (LxWxD) dimensions, 5kg weight, RAL9017 Traffic Black color.


### Product Overview

Product name	Kalani IP66 28KLM 840 WB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579621
Fixture luminous flux (lm)	30800
Luminaire efficacy (lm/W)	156
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Photobiological Risk Group	RG1
Total power consumption (W)	198
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No


## Kalani IP66 28KLM 840 WB 0056716

LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP66
IK rating	IK08
Product EAN number	5410288567167
Warranty	5 years
Dimming method	N/A

### Photometry



### Technical drawings



### Data table

#### GENERAL DATA

Product name	Kalani IP66 28KLM 840 WB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001744
E-number FI	4579621
Warranty	5 years

#### OPTICAL DATA

Fixture luminous flux (lm)	30800
Luminaire efficacy (lm/W)	156
Colour temperature (K)	4000
Light colour	Neutral White

## Kalani IP66 28KLM 840 WB 0056716

CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Distribution type	Symmetric
Photobiological Risk Group	RG1

### ELECTRICAL DATA

Total power consumption (W)	198
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	840
Inrush Current (A)	80
Inrush Duration (µs)	350
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	6
Max. products per 13A C Breaker	8
Max. products per 16A C Breaker	10
Max. products per 20A C Breaker	12
Max. products per 10A B Breaker	5
Max. products per 13A B Breaker	7
Max. products per 16A B Breaker	8
Max. products per 20A B Breaker	10

## Kalani IP66 28KLM 840 WB 0056716

Mains surge immunity (differential mode -> L-N) (kV)	10
Mains surge immunity (common mode -> L/N - GND) (kV)	10
Connectable conductor cross section - Min (mm <sup>2</sup> )	1
Connectable conductor cross section - Max (mm <sup>2</sup> )	1

### LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	97000
Lifespan L80 B20	89000

### PHYSICAL DATA

Housing colour	RAL 9017 - Traffic black
IP rating	IP66
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	Glass
Reflector finish	Matt
Nominal Product Length (mm)	450
Nominal Product Width (mm)	335
Nominal Product Height (mm)	75
Weight (kg)	5.0

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288567167
Packaging single length / height (cm)	50.5
Packaging single width (cm)	38.0
Packaging single depth (cm)	14.0
DUN14 (outer)	05410288567167
Units per outer package	1

Kalani IP66 28KLM 840 WB  
0056716

Packaging outer length / height (cm)	50.5
Packaging outer width (cm)	38.0
Packaging outer depth (cm)	14.0

## SAFETY DATA

Optimal operating condition (°C)	-30-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No