



Color: ■ silver-colored Similar to illustration

Electrical data

Ratings per IEC/EN	
Rated current	76 A

Physical data

Pin spacing	20 mm / 0.787 inches
Jumper assignment	1-2-3-4-5

Mechanical data

Suitable	for 745 Series (16 mm²) and 2716 Series
----------	---

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Contact material	Copper alloy
Contact Plating	Tin
Fire load	0 MJ
Weight	12.5 g

Commercial data

Product Group	4 (Printed Circuit Connectors)
PU (SPU)	200 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4044918303569
Customs tariff number	85366990990



Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 745-685

↓

Documentation

Additional Information

Technical Section

03.04.2019

pdf

2027.26 KB

↓


CAD/CAE-Data

CAD data


2D/3D Models 745-685

↓


Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.