



Features

- Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 4000K, CRI80, Non-dimmable, 29000lm, 198W, 146lm/W, Asymmetrical Wide beam, 100.000hrs L70B50 lifespan, 450 x 335 x 75mm (LxWxD) dimensions, 5kg weight, RAL9017 Traffic Black color.


Product Overview

Product name	Kalani IP66 28KLM 840 ASYM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579622
Fixture luminous flux (lm)	29000
Luminaire efficacy (lm/W)	146
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	65x120
Photobiological Risk Group	RG1
Total power consumption (W)	198
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Low (6% - 20%)

Kalani IP66 28KLM 840 ASYM 0056717

Housing colour	RAL 9017 - Traffic black
IP rating	IP66
IK rating	IK08
Product EAN number	5410288567174
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

