


Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI
2023580




PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	118
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768235803

PHOTOMETRY

Optix Recessed 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI
2023580



Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.78	0.78	898
1.0	1.55	1.55	224
1.5	2.33	2.33	99
2.0	3.10	3.10	62
2.5	3.88	3.88	39
3.0	4.65	4.65	26

TECHNICAL DRAWINGS

