### **DEMKO CERTIFICATE**

Certificate No. D-09102

**Page** 1/4

**Date of Issue** 2022-02-14

Certificate Holder NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

BELGIUM

Manufacturer NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

**BELGIUM** 

Production site NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

**BELGIUM** 

Certified Product Push-button switches

**Model** 7\*\*-33000+-37, 7\*\*-33000+-31, 7\*\*-35000+-350, 7\*\*-35000+-351, 7\*\*-35910+-

350, 7\*\*-83101, 7\*\*-83201, 7\*\*-84101, 7\*\*-84111, 7\*\*-84102, 7\*\*-84112, 7\*\*-84201, 7\*\*-84201, 7\*\*-84202, 7\*\*-84

84902, 7\*\*-73000, 7\*\*-74000, 7\*\*-75000 See page 2 for additional Information

Trademark NIKO

Ratings Pattern 4 and 6 10A 250V~, IP55

Tested according to EN 60669-1:2018

**Test Report No.** 4790159027-002 issued on 2021-12-23

**Additional** 

**Expire date** 2028-05-24

Certification Manager

Jan-Erik Storgaard

This is to certify that representative sample(s) of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the D-Mark Requirements. As specified in the respective appendix below the Designated Certificate holder is entitled to use the D-Mark, or its alternative for cables, for the Certified Product manufactured at the production site(s) identified above, in accordance with the D-Mark Service Agreement, including without limitation the D-Mark Testing and Certification Services Service Terms. Only those Products bearing the D-Mark should be considered as being covered by UL's D-Mark Service. This Certificate shall remain valid through the expiration date, unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the expiration date.

**Certification Body** 

UL International Demko A/S, Borupvang 5A, DK-2750 Ballerup, Denmark, Tel. +45 44 85 65 65, info.dk@ul.com www.UL.com



# **Appendix DEMKO CERTIFICATE**

Certificate No. D-09102

Page 2/4

**Date of Issue** 2022-02-14

### Additional Model(s):

Push-button switches screw-type terminals

7**-33000+-37	pattern 6 push-button (control) + single actuating member, 10A 250V ~
7** 22000 . 24	nottone Couch button a single potanting magneton 104 0501/

7\*\*-33000+-31 pattern 6 push-button + single actuating member, 10A 250V ~

7\*\*-35000+-350 pattern 6 push-button+6 push-button + double actuating member, 10A 250V ~

7\*\*-35000+-351 pattern 6 push-button (control) +6 push-button (control) + double actuating member, 10A 250V ~

7\*\*-35910+-350 pattern 4 2xpush-button + double actuating member, 10A 250V ~

#### Boxes:

/**-83101	surface mounting box for 1 function with membranes
7**-83201	vertical surface mounting box for 2 functions with membranes
7**-84101	surface mounting box for 1 function with 1 M20 entry
7**-84111	surface mounting box for 1 function with 2x1 M20 entry
7**-84102	surface mounting box for 1 function with 1x2 M20 entries
7**-84112	surface mounting box for 1 function with 1x2 M20 entries + 1 M20 entry
7**-84201	vertical surface mounting box for 2 functions with 1 M20 entry
7**-84211	vertical surface mounting box for 2 functions with 2x1 M20 entry
7**-84202	vertical surface mounting box for 2 functions with 1x2 M20 entries
7**-84212	vertical surface mounting box for 2 functions with 1x2 M20 entries + 1 M20 entry
7**-84302	vertical surface mounting box for 3 functions with 1x2 M20 entries
7**-84801	horizontal surface mounting box for 2 functions with 1 M20 entry
7**-84802	horizontal surface mounting box for 2 functions with 1x2 M20 entries
7**-84902	horizontal surface mounting box for 3 functions with 1x2 M20 entries
7**-73000	flush mounting box for 1 function
7**-74000	vertical flush mounting box for 2 functions
7**-75000	horizontal flush mounting box for 2 functions

### 7\*\* can refer to the following colors:

**Certification Body** 

-700: grey -701: white -761: black



## **Appendix DEMKO CERTIFICATE**


Certificate No. D-09102

**Page** 3/4

**Date of Issue** 2022-02-14

#### **Certification Mark D-Mark**

The D-Mark, as displayed below, shall appear on certified products only. Except as specified below the Mark shall be legible and no Minimum size is specified.



The size of the Mark may be reduced or enlarged on the condition that it remains readable and that the proportions of width and height are kept. The use of dark text for the D-Mark on light backgrounds and light text on dark backgrounds is permitted.

The D-Mark may appear on a label, nameplate, or may be cast, stamped or molded into the product. When appearing on a label or nameplate, the Manufacturer's name or trademark along with a model number are also required on that same label or nameplate. If cast, stamped or molded, the Certificate Manufacturer's name or trademark and model number shall also appear elsewhere on the product

When putting the product on the EU market, the manufacturer's name, trademark or mark of origin must be affixed in a clearly visible location and position on the product, on the package and in the user manual. It can be affixed by label, be directly imprinted, or cast or molded into the product.

Where the size of the product does not allow the Mark, the manufacturer's name, trademark, mark of origin and model number to be legible, and appearance on a label is not desired, it is allowed to cast, stamp or mold the Mark into the product, in a size which is not visible to the naked eye, provided the legible Mark, the manufacturer's name, trademark or mark of origin and model number appears on the package and in the user manual



# **Appendix DEMKO CERTIFICATE**

2022-02-14

Certificate No. D-09102 **Page** 4/4 Date of Issue

### Alternate certification Mark for cables

As an alternative to the D-Mark specified above the alternate D-Mark, displayed below, can appear on certified cables only. Minimum size is not specified, as long as the mark is legible.

⊲DEMKO⊳

The alternate D-Mark may be cast, stamped or molded into the cable and continue throughout the length of the cable as specified in the applicable cable standard.

All content shall be in accordance with the details provided on this D-Mark Certificate.

