

# Product data sheet Spirotech

## Product name

**SpiroTrap -DN200 -Flange**

## Article number

**BE200F**


## Product properties

A steel dirt separator for standard flow rate (1.5 m/s) with a DN50 - DN300 PN16 flange connection.

- Very small particles, from 5  $\mu\text{m}$  (= 0.005 mm) are separated and removed
- Dirt can be drained while the system is in operation
- No shut-off valves or bypass required
- Applicable with 50/50 Ethylene Glycol / Water (Volume)
- Constant low pressure drop
- Maintenance only takes a few seconds
- No unnecessary downtime
- PN16 flange connections
- Connection diameters from DN50 - DN300, larger connection diameters on request



## Product dimensions



# Product data sheet Spirotech

## ETIM product data

|                          |                |                                       |           |
|--------------------------|----------------|---------------------------------------|-----------|
| Housing material         | Steel          | Article compression class             | PN 10     |
| With drain valve         | Yes            | Surface protection                    | Lacquered |
| Housing material quality | St 37 (1.0254) | Suitable for open system              | No        |
| Backwash filter          | No             | Suitable for closed system            | Yes       |
| Max. operating pressure  | 10 bar         | Suitable for solar                    | No        |
| Variable flow direction  | Yes            | With dismountable filter              | No        |
| With insulation          | No             | Filter volume                         | 105 l     |
| Separator type           | Dirt           | Magnet operating principle            | No        |
| Connection               | Flange         | With automatic de-aerator             | No        |
| Model                    | Horizontal     | With integrated replenishment automat | No        |
| Nominal diameter         | DN 200         | With couplers                         | No        |
| Max. glycol mixture      | 50 %           | Cleaning possible during operation    | Yes       |
| Suitable for heating     | Yes            | Material of connection                | Steel     |
| Suitable for cooling     | Yes            | Inlet/outlet offset distance          | 0 mm      |
| Construction length      | 775 mm         | Flange standard                       | DIN       |

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

