

## VSK-161616: Extension or body for manifold, 3 SK connections Ø16



### Commercial information

Synthetic manifold or extension with SK connectors Ø16

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 30 mm    |
| Length     | 174 mm   |
| Width      | 66 mm    |
| Net weight | 0.151 kg |

#### Certificates

QB (CSTBat), ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, KOMO, STF, GOST-R, TSU, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                    |  |                                      |                    |
|------------------------------------|--|--------------------------------------|--------------------|
| Suitable for tap water             | ✓  | Outer pipe diameter connection 1     | 16 Millimetre      |
| Suitable for central heating water | ✓  | Outer pipe diameter connection 2     | 0 Millimetre       |
| Suitable for cooling water         | ✓  | Number of branches                   | 3                  |
| Suitable for compressed air        | ✗  | Number of branching directions       | 1                  |
| Suitable for glycol                | ✓  | Distance between offset              | 50 Millimetre      |
| Mounting method                    | Surface mounting                               | Max. medium temperature (continuous) | 70 Degrees celsius |
| Model                              | Distributor/collector                          | Width                                | 66 Millimetre      |
| Material                           | Plastic  | Height                               | 30 Millimetre      |
| Material quality                   | Polyvinylidene fluoride (PVDF)                 | Length distributor                   | 174 Millimetre     |
| Surface protection                 | Untreated                                      |                                      |                    |
| Shape                              | Throughflow with straight branches             |                                      |                    |
| Connection 1                       | Insert (push-fitting)                          |                                      |                    |
| Nominal diameter connection 2      | 3/4 inch (20)                                  |                                      |                    |
| Connection 2                       | External thread cylindrical BSPP-G (ISO 228-1) |                                      |                    |
| Nominal diameter branches          | DN 15  |                                      |                    |
| Connection branches                | Other  |                                      |                    |
| Deviant distance between branches  | ✗  |                                      |                    |
| With filling/drain tap             | ✗  |                                      |                    |
| System specific                    | ✓  |                                      |                    |
| With shut-off valve                | ✗  |                                      |                    |
| With de-aeration                   | ✗  |                                      |                    |
| With wall-mounting bracket         | ✗  |                                      |                    |
| With mounting material             | ✗  |                                      |                    |
| With legs                          | ✗  |                                      |                    |
| With insulation                    | ✗  |                                      |                    |
| KOMO certified                     | ✓  |                                      |                    |
| Type approval according to BBR/EKS | ✗  |                                      |                    |