



Features


- 5 metre IP67 LED reel with pre-attached 3M adhesive type; equipped with 800 LEDs; 7900lm per 5m; 24V; 3000K; CRI90; R9>50; SDCM≤3;Compatible with emergency packs: 0046600, 0046601

Product Overview


Product name	Flex Pro IP67 7900lm 930
Technology	LED
Mount	Other
General application	Hospitality
ETIM Class	EC002706
Fixture luminous flux (lm)	7900
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	63
Electrical protection	Class III
Dimmable	Yes
IP rating	IP67
IK rating	IK00
Product EAN number	5410288682044
Warranty	5 years
Dimming method	Other

Flex Pro IP67 7900lm 930
0068204

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Flex Pro IP67 7900lm 930
---------------------	--------------------------

Flex Pro IP67 7900lm 930 0068204

Technology	LED
Mount	Other
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	7900
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	63
Primary Supply/Product voltage - min (V)	24.0
Primary Supply/Product voltage - max (V)	24.0
Electrical protection	Class III
Control gear required	Yes
Dimmable	Yes
Dimming method	Other
Drive current (mA)	2600
Glow Wire Test (°C)	650
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	N/A

LIFETIME DATA

Lifespan L70 B50	54000
Lifespan L80 B20	54000



Flex Pro IP67 7900lm 930
0068204

Lifespan L90 B10	36000
------------------	-------

PHYSICAL DATA

IP rating	IP67
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	12
Nominal Product Height (mm)	4
Weight (kg)	0.35


PACKAGING

Single packaging type	Carton
Product EAN number	5410288682044
Packaging single length / height (cm)	29.5
Packaging single width (cm)	27.5
Packaging single depth (cm)	3.0
DUN14 (outer)	15410288682041
Units per outer package	10
Packaging outer length / height (cm)	31.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	30.0

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No


Energy label



63
kWh/1000h



2019/2015



63
kWh/1000h



2019/2015