

## PRODUCT DATASHEET

**Type:** eFLOOR-PRO-200-145  
**Art. Nr.:** 34201



9120015724591

**Short description**

Heating mat extra thin 3,8mm, PFAS free, 0.7m<sup>2</sup>, 50x145cm, 145W, 230V

**Product Description**

The eFLOOR PRO self-adhesive mesh heating mat has been specially developed for use under tile and stone floors and is suitable for comfortable floor heating, complete room heating, or cold insulation on walls. Thanks to its low overall height of only 3.8 mm, the mat can also be used in renovations without any problems, as it requires only a minimal installation height. Factory assembly enables quick and easy installation. The heating mat has a dipole design with only one connection cable, which further simplifies installation and saves time. The PFAS-free heating conductor is low in magnetic fields and offers high stability in the tile adhesive bed thanks to its robust structure. The self-adhesive carrier mesh with a 12×12 mm grid ensures secure fixation to the substrate. eFLOOR PRO is available in five different power levels from 60 to 200 W/m<sup>2</sup>, allowing it to be flexibly adapted to different requirements and room conditions. Customized designs in individual sizes, power ratings, voltages, or shapes are also available on request. The nominal temperature of the heating conductor is up to 90 °C. The system complies with protection class IPX7 and is designed in accordance with VDE 0700. The eFLOOR PRO heating mat is CE-compliant and VDE-tested. The heating conductor is designed using dipole technology, is PFAS-free, and has a low magnetic field. The grid spacing is 12×12 mm, and the heating conductor thickness is 3.2 mm. The connection cable is 4 m long and consists of 2×1.0 mm<sup>2</sup> with integrated protective braiding. The operating voltage is 230 V. As a protective measure, a residual current circuit breaker (RCCB) with a 30 mA tripping current is required. This product is a stationary, electric floor heating device for individual rooms; in order to meet the binding ecodesign requirements of Commission Regulation (EU) 2024/1103, it must be supplemented by a controller that fulfills at least the following control functions: electronic room temperature controller with weekday control (TW) and at least one f function (e.g., f2 or f4); the following combinations are possible: TW (f2), TW (f3), TW (f4), TW (f8)

**ETIM 10 Characteristics**

|                                            |       |                                  |                           |
|--------------------------------------------|-------|----------------------------------|---------------------------|
| <b>Model</b>                               | Other | <b>Connection voltage</b>        | 230 23 Volt<br>0          |
| <b>With support mat</b>                    | ✓     | <b>Connected load</b>            | 150 15 Watt<br>0          |
| <b>Fixation thermal conductor</b>          | Glued | <b>Power</b>                     | 200 Watt per square metre |
| <b>Self-adhesive</b>                       | ✓     | <b>Heating conductor load</b>    | 10 Watt per metre         |
| <b>Suitable for damp space</b>             | ✓     | <b>Resistance</b>                | 353 Ohm                   |
| <b>Suitable as outdoor surface heating</b> | ✗     | <b>Number of cold conductors</b> | 1                         |
| <b>Suitable as roof surface heating</b>    | ✗     | <b>Length of cold conductors</b> | 3000 Millimetre           |
| <b>With controller</b>                     | ✗     | <b>Surface</b>                   | 0.7 Square metre          |
| <b>With room temperature controller</b>    | ✗     | <b>Length</b>                    | 1450 Millimetre           |
| <b>With floor temperature sensor</b>       | ✗     | <b>Width</b>                     | 500 Millimetre            |
|                                            |       | <b>Thickness</b>                 | 3.2 Millimetre            |

Created on: 16/12/2025