



Color: ■ silver-colored      Similar to illustration

Electrical data

| Ratings per IEC/EN |      |
|--------------------|------|
| Rated current      | 32 A |

Physical data

|                   |                       |
|-------------------|-----------------------|
| Pin spacing       | 7.5 mm / 0.295 inches |
| Jumper assignment | 1-2                   |

Mechanical data

|          |                        |
|----------|------------------------|
| Suitable | for 745 Series (4 mm²) |
|----------|------------------------|

Material data

|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| Note (material data) | <a href="#">Information on material specifications can be found here</a> |
| Color                | silver-colored                                                           |
| Contact material     | Copper alloy                                                             |
| Contact Plating      | Tin                                                                      |
| Fire load            | 0 MJ                                                                     |
| Weight               | 0.9 g                                                                    |

Commercial data

|                       |                                |
|-----------------------|--------------------------------|
| Product Group         | 4 (Printed Circuit Connectors) |
| PU (SPU)              | 250 (50) pcs                   |
| Packaging type        | Box                            |
| Country of origin     | CH                             |
| GTIN                  | 4044918303347                  |
| Customs tariff number | 85366990990                    |



| Product Classification |                      |
|------------------------|----------------------|
| UNSPSC                 | 39121421             |
| eCl@ss 10.0            | 27-14-11-40          |
| eCl@ss 9.0             | 27-44-04-92          |
| ETIM 9.0               | EC000489             |
| ETIM 8.0               | EC000489             |
| ECCN                   | NO US CLASSIFICATION |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 745-192

↓

Documentation

Additional Information

Technical Section

03.04.2019

pdf  
2027.26 KB

↓


CAD/CAE-Data

CAD data


2D/3D Models 745-192

↓


Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.