Data Sheet | Item Number: 745-583
Jumper; 3-way; silver-colored

https://www.wago.com/745-583

Color: ▨ silver-colored

Similar to illustration

Electrical data

Ratings per IEC/EN

Rated current	76 A

Physical data

Pin spacing	10 mm / 0.394 inches
Jumper assignment	1-2-3

Mechanical data

Suitable	for 745 Series (16 mm²) and 2716 Series

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Contact material	Copper alloy
Contact Plating	Tin
Fire load	0 MJ
Weight	5.6 g

Commercial data

Product Group	4 (Printed Circuit Connectors)
PU (SPU)	300 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4044918303491
Customs tariff number	85366990990

Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 745-583

Documentation

Additional Information

| Technical Section | 03.04.2019 | pdf 2027.26 KB | |

CAD/CAE-Data

CAD data

2D/3D Models 745-583

CAE data

ZUKEN Portal 745-583

Installation Notes

Inserting a comb-style jumper bar.

To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.

To remove the jumper bar, lift it up using a screwdriver – 745 Series.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at:: www.wago.com