

## 6PK-5007-X: Bend 90° female adapter 50x5/4" inox



### Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)\*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 57 mm    |
| Length     | 129 mm   |
| Width      | 105 mm   |
| Net weight | 0.372 kg |

#### Certificates

KIWA, ATG, QB (CSTBat), DVGW Wasser, ETA, ÖVGW Wasser, SINTEF, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, AFNOR, PZH, ACS, DNV-GL, Aenor, Sans 21003, RISE, EMI

#### Applications

Potable water, Heating, Compressed air, Cooling, Demi Water, Sanitary

#### Solutions

Building installations, Industry, Laboratory, Utility, Shipbuilding

## Technical characteristics

|                                    |                                                |                                  |                        |
|------------------------------------|------------------------------------------------|----------------------------------|------------------------|
| Material connection 1              | Polyvinylidene fluoride (PVDF)                 | Outer pipe diameter connection 1 | 50 Millimetre          |
| Material quality connection 1      | Polyvinylidene fluoride (PVDF) (expired)       | Zeta value                       | 1.753                  |
| Surface protection connection 1    | Untreated                                      | Length                           | 128.5 Millimetre       |
| Surface treatment connection 1     | Untreated                                      | Length of connection 1           | 100 Millimetre         |
| Material connection 2              | Stainless steel                                | Working length connection 1      | 49 Millimetre          |
| Material quality connection 2      | Stainless steel 316 L (1.4404)                 | Length of connection 2           | 76.5 Millimetre        |
| Surface protection connection 2    | Untreated                                      | Working length connection 2      | 56.5 Millimetre        |
| Surface treatment connection 2     | Untreated                                      | Wrench width                     | 0 Millimetre           |
| Shape                              | Bend                                           | Wrench width union nut           | 0 Millimetre           |
| Reducing                           | ✗                                              | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Eccentric                          | ✗                                              | Max. operating pressure at 20 °C | 10 Bar                 |
| System specific                    | ✓                                              | Standard Dimension Ratio (SDR)   | 0                      |
| Connection 1                       | Press sleeve                                   |                                  |                        |
| Nominal diameter connection 2      | 1 1/4 inch (32)                                |                                  |                        |
| Connection 2                       | Internal thread cylindrical BSPP-G (ISO 228-1) |                                  |                        |
| Main colour fitting                | Black                                          |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM) |                                  |                        |
| With buffer stud                   | ✓                                              |                                  |                        |
| High tensile strength              | ✗                                              |                                  |                        |
| With thermal insulation            | ✗                                              |                                  |                        |
| Ring stiffness class               | Other                                          |                                  |                        |
| With sealing rings/gaskets         | ✓                                              |                                  |                        |
| Capped                             | ✗                                              |                                  |                        |
| With drain valve                   | ✗                                              |                                  |                        |
| With de-aerator                    | ✗                                              |                                  |                        |
| FM quality mark                    | ✗                                              |                                  |                        |
| LPCB quality mark                  | ✗                                              |                                  |                        |
| ULC quality mark                   | ✗                                              |                                  |                        |
| UL quality mark                    | ✗                                              |                                  |                        |
| DIN-CERTCO certificate             | ✗                                              |                                  |                        |
| VdS quality mark                   | ✗                                              |                                  |                        |
| With approval for TÜV              | ✗                                              |                                  |                        |
| DVGW quality mark for gas          | ✗                                              |                                  |                        |
| DVGW quality mark for water        | ✓                                              |                                  |                        |
| KIWA certified                     | ✓                                              |                                  |                        |
| Gastec QA mark                     | ✗                                              |                                  |                        |
| KOMO certified                     | ✓                                              |                                  |                        |
| Type approval according to BBR/EKS | ✗                                              |                                  |                        |