


Optix Recessed 600x600 Standard Output  
*OPTIX RECESSED 600x600 2L SO 3000K ALU DALI*  
2023591



PRODUCT OVERVIEW

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| Product name                    | OPTIX RECESSED 600x600 2L SO 3000K ALU DALI |
| Technology                      | LED (3 SDCM)                                |
| Cap/Base                        | N/A                                         |
| Housing                         | Steel                                       |
| Mount                           | Ceiling recessed mounting                   |
| Fixture rating                  | Enclosed                                    |
| Warranty                        | 5 years                                     |
| Fixture luminous flux (lm)      | 2900                                        |
| Luminaire efficacy (lm/W)       | 126                                         |
| Colour temperature (K)          | 3000                                        |
| Light colour                    | Warm White                                  |
| CRI (Ra)                        | 80                                          |
| Colour Variation Initial (SDCM) | SDCM3                                       |
| Glare control                   | < 19                                        |
| Photobiological Risk Group      | RG0                                         |
| Total power consumption (W)     | 23                                          |
| Electrical protection           | Class I                                     |
| Control gear type               | LED driver constant current                 |
| LED Flickering Rate             | Ultra low (5% or less)                      |
| Housing colour                  | RAL 9016 - Traffic white / Bezel            |
| IP rating                       | IP20                                        |
| IK rating                       | IK07                                        |
| Product EAN number              | 5025768235919                               |

DATA TABLE

|              |                                             |
|--------------|---------------------------------------------|
| General data |                                             |
| Product name | OPTIX RECESSED 600x600 2L SO 3000K ALU DALI |
| Technology   | LED (3 SDCM)                                |
| Cap/Base     | N/A                                         |
| Housing      | Steel                                       |
| Mount        | Ceiling recessed mounting                   |

## Optix Recessed 600x600 Standard Output

*OPTIX RECESSED 600x600 2L SO 3000K ALU DALI*

### 2023591

|                                         |          |
|-----------------------------------------|----------|
| Fixture rating                          | Enclosed |
| Performance ambient temperature Tq (°C) | 25       |
| Warranty                                | 5 years  |

#### Optical data

|                                 |            |
|---------------------------------|------------|
| Fixture luminous flux (lm)      | 2900       |
| Luminaire efficacy (lm/W)       | 126        |
| Colour temperature (K)          | 3000       |
| Light colour                    | Warm White |
| CRI (Ra)                        | 80         |
| Colour Variation Initial (SDCM) | SDCM3      |
| Glare control                   | < 19       |
| Photobiological Risk Group      | RG0        |

#### Electrical data

|                                                          |                             |
|----------------------------------------------------------|-----------------------------|
| Total power consumption (W)                              | 23                          |
| Primary Supply/Product voltage - min (V)                 | 198.0                       |
| Lamp power factor                                        | 0.98                        |
| Electrical protection                                    | Class I                     |
| Control gear type                                        | LED driver constant current |
| Drive current (mA)                                       | 225                         |
| Inrush Current (A)                                       | 29                          |
| Inrush Duration (µs)                                     | 180                         |
| Glow Wire Test (°C)                                      | 850                         |
| Energy Efficiency Class (A->G) of contained light source | C                           |
| Nominal Frequency (Hz)                                   | 50/60Hz                     |
| LED Flickering Rate                                      | Ultra low (5% or less)      |
| Max. products per 10A C Breaker                          | 21                          |
| Max. products per 20A B Breaker                          | 27                          |
| Connectable conductor cross section - Min (mm²)          | 2.5                         |
| Connectable conductor cross section - Max (mm²)          | 2.5                         |

#### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 120000 |
| Lifespan L80 B20 | 107500 |
| Lifespan L90 B10 | 48500  |

#### Physical data

|                             |                                  |
|-----------------------------|----------------------------------|
| Housing colour              | RAL 9016 - Traffic white / Bezel |
| IP rating                   | IP20                             |
| IK rating                   | IK07                             |
| Diffuser finish             | Matt/satinized                   |
| Diffuser material           | PC Polycarbonate                 |
| Nominal Product Length (mm) | 596                              |
| Nominal Product Width (mm)  | 596                              |
| Weight (kg)                 | 5.0                              |



## Optix Recessed 600x600 Standard Output

*OPTIX RECESSED 600x600 2L SO 3000K ALU DALI*  
2023591

### Packaging

|                                      |                |
|--------------------------------------|----------------|
| Single packaging type                | Carton         |
| Product EAN number                   | 5025768235919  |
| Packaging single width (cm)          | 6.5            |
| Packaging single depth (cm)          | 65.0           |
| DUN14 (outer)                        | 05025768235919 |
| Packaging outer length / height (cm) | 62.0           |

### PHOTOMETRY



### TECHNICAL DRAWINGS

