



Color: white

Technical data	
Suitable	for wire cross-section 6 ... 16 mm²
Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	1000 pcs/reel; 2 lines
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.22 mm

Mechanical data	
Mounting type	Sliding on conductor
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	313 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-06-29
ETIM 9.0	EC001530
ETIM 8.0	EC001530
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143082839
Customs tariff number	39269097900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 211-863

↓

Documentation

Operating Instructions

211-861 Information on printing material

1

28.08.2020

pdf

1244.38 KB

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking


1.1.1.1 Marking device



[Item No.: 258-5000](#)
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material

Installation Notes

Application



Conductor marker for thread-on mounting