



Color: ■ gray

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated impulse withstand voltage (III / 3)	6 kV
Rated current	24 A

Physical data

Width	4.5 mm / 0.177 inches
Height	6 mm / 0.236 inches
Jumper assignment	1-2

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.008 MJ
Weight	1.3 g

Commercial data	
Product Group	17 (TOP JOB Installation Terminal Blocks)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918270830
Customs tariff number	85366990990

Product Classification	
UNSPSC	39121410
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 780-452	↓

Documentation

Bid Text			
780-452	19.02.2019	xml 2.91 KB	↓
780-452	28.04.2017	doc 24.00 KB	↓

CAD/CAE-Data

CAD data	
2D/3D Models 780-452	↓

CAE data	
EPLAN Data Portal 780-452	↓
WSCAD Universe 780-452	↓
ZUKEN Portal 780-452	↓

Installation Notes

Commoning



Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!