

AD-EKEK: Straight coupling eurocone 3/4" male



Commercial information

Transition fitting with 2x eurocone connectors (3/4"M)

Basic unit dimensions

Height	31 mm
Length	29 mm
Width	31 mm
Net weight	0.060 kg

Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, DIN CERTCO, CE, DNV-GL, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Length	29 Millimetre
Material connection 2	Brass	Wrench width union nut	0 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Medium temperature (continuous)	-10 60 Degrees celsius
Shape	Straight	Max. operating pressure at 20 °C	10 Bar
Reducing	✗	Standard Dimension Ratio (SDR)	0
Eccentric	✗		
System specific	✓		
Nominal diameter connection 1	3/4 inch (20)		
Connection 1	Compression ring		
Nominal diameter connection 2	3/4 inch (20)		
Main colour fitting	Brass		
With buffer stud	✗		
Self-sealing	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
VdS quality mark	✗		
KIWA certified	✓		
Gastec QA mark	✗		