

Splashproof blind plate, grey

700-38500



This blind plate is mounted directly onto a splashproof mounting box and made of ABS. It is used to cleanly close off connection points for later system expansions or to install non-standard functions. Colour: grey.



Technical data

Splashproof blind plate, grey.

- Colour: grey
- Colour RAL (approximately): 7035
- Colour NCS (approximately): NCS S 1502-B
- Surface treatment: coloured in mass
- Hinged lid: Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed
- Number of lenses: 0
- Number of mechanisms: 1
- Material finishing: the blind plate is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The blind plate itself is made of rigid ABS
- Markings on the flush-mounting frame: indelibly indicated at the rear side: terminals
- Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: see protection degree of the mounted function
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Marking: CE