

Specifications



Photo is representative



Eaton BK/SC-3

Eaton Bussmann series SC fuse, Current-limiting fast acting fuse, Rejection style, 3 A, Class G, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 170 Vdc, 100 kAIC at 600 Vac, Bulk, 600 V, 170 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	BK/SC-3
UPC	051712750400
EAN	5027590408332
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.31 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant
CATALOG NOTES	Bulk
PRODUCT TYPE	Fuse

Electrical rating

AMPERAGE RATING	3 A
INTERRUPT RATING	10 kAIC at 170 Vdc 100 kAIC at 600 Vac
VOLTAGE RATING	600 Vac, 170 Vdc

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Rejection style

Physical details

PACKAGING TYPE	Standard Bulk
----------------	------------------

Resources

	BK/SC-3~BK-SC-3~BUSS SC FUSE CLASS G
CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/SC-3

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

