

# Data Sheet | Item Number: 279-483

Jumper; 3-way; insulated; gray

<https://www.wago.com/279-483>



Color: ■ gray

## Electrical data

### Ratings per IEC/EN

|               |      |
|---------------|------|
| Rated current | 15 A |
|---------------|------|

## Physical data

|                   |                        |
|-------------------|------------------------|
| Width             | 12 mm / 0.472 inches   |
| Height            | 3.89 mm / 0.153 inches |
| Jumper assignment | 1-2-3                  |

## Material data

|                      |  |
|----------------------|--|
| Note (material data) | <a href="#">Information on material specifications can be found here</a> |
| Color                | gray   |
| Fire load            | 0.007 MJ   |
| Weight               | 1 g  |

## Commercial data

|                       |               |
|-----------------------|---------------|
| PU (SPU)              | 200 (25) pcs  |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4044918610445 |
| Customs tariff number | 85366990990   |

| Product Classification |                      |
|------------------------|----------------------|
| UNSPSC                 | 39121421             |
| eCl@ss 10.0            | 27-14-11-40          |
| eCl@ss 9.0             | 27-14-11-40          |
| ETIM 9.0               | EC000489             |
| ETIM 10.0              | EC000489             |
| ECCN                   | NO US CLASSIFICATION |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

## Downloads

### Environmental Product Compliance

| Compliance Search                        |                   |
|--|-------------------|
| Environmental Product Compliance 279-483 | <a href="#">↓</a> |

## Documentation

| Bid Text |            |                 |                   |
|----------|------------|-----------------|-------------------|
| 279-483  | 19.02.2019 | xml<br>2.54 KB  | <a href="#">↓</a> |
| 279-483  | 27.04.2017 | doc<br>23.50 KB | <a href="#">↓</a> |

## CAD/CAE-Data

| CAD data             |                   |
|----------------------|-------------------|
| 2D/3D Models 279-483 | <a href="#">↓</a> |

| CAE data               |                   |
|------------------------|-------------------|
| WSCAD Universe 279-483 | <a href="#">↓</a> |
| ZUKEN Portal 279-483   | <a href="#">↓</a> |

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Tool

##### 1.1.1.1 Operating tool



**Item No.: 279-433**  
 Operating tool; made of insulating material; 3-way

## Installation Notes

### Commoning



Commoning using comb-style jumper bars.  
Push comb-style jumper bars down until fully inserted.

### Commoning



4-conductor through terminal blocks, angled type, formation of groups with 3-way, comb-style jumper bars

### Commoning



Carrier terminal blocks with component plugs, alternate comb-style jumper bars, 3-way comb-style jumper bar

### Commoning



Commoning front-entry disconnect terminal blocks via comb-style jumper bar using a 10-pole operating tool