



Features

• Integrated LED spotlight, Textured Black - RAL9005, simple and slick integral design with no driver box and without any visible screws, ideal for retail applications, die-cast aluminium body, passive cooling heatsink. Beam angle: 36°, additional lenses 24° and 54° beam angle included, color temperature: 3000K , total system power: 15W, total fixture output: 1496 lm, LOR: 100%, colour rendering: Ra: 90 typical, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, ultra low LED flickering rate (5% or less), power factor: >0.90, electrical protection: Class I, Powergear 3-circuit adapter suitable for 3-circuit tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 345°, vertical tilt: 90°, dimensions: Ø60x70x245, weight: 0.517kg.


Product Overview

Product name	Pixo Small 1490lm 930 NB MB WB BLK
Technology	LED
Cap/Base	N/A
Environment	Indoor
E-number FI	4278240
Fixture luminous flux (lm)	1496
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG1
Total power consumption (W)	15
Electrical protection	Class I

Pixo Small 1490lm 930 NB MB WB BLK
0005441

IP rating	IP20
IK rating	IK03
Product EAN number	5410288054414
Warranty	5 years

Photometry



Technical drawings

