

Splashproof key switch 16 A with screw terminals and two unique keys, grey

700-38810



With this splashproof key switch you can easily open and close electric sliding doors, fences, swimming pool covers, etc. The key switch has three positions (1-0-2) and the key can be removed in any position. Two unique keys are delivered as standard with the order. The key switch is compatible with all Niko Hydro flush-mounting and surface-mounting boxes. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and ammonia-rich environments.

Technical data

Splashproof key switch 16 A with screw terminals and two unique keys, grey.

- Maximum MCB rating: 16 A (1.5 mm²) / 20 A (2.5 mm²) (limited by national installation rules)
- Colour: grey
- Colour RAL (approximately): 7035
- Colour NCS (approximately): NCS S 1502-B
- Surface treatment: coloured in mass
- Material base insert:
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Terminals wire capacity: 2 x 2.5 mm²
- Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a function and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Dimensions (HxWxD): 72.7 mm x 72.7 mm x 66.5 mm
- Marking: CE



Wiring diagram

