

# Data Sheet | Item Number: 2002-424/000-006

Continuous jumper; from 1 to 4; insulated; blue

<https://www.wago.com/2002-424/000-006>



Color: ■ blue

## Electrical data

### Ratings per IEC/EN

Nominal voltage (III/3)	800 V
Rated impulse withstand voltage (III / 3)	8 kV
Rated current	25 A

## Physical data

Width	10.9 mm / 0.429 inches
Height	4.1 mm / 0.161 inches
Depth	18.5 mm / 0.728 inches
Jumper assignment	1-4

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	blue
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	V0
Fire load	0.012 MJ
Weight	1.1 g

**Commercial data**

PU (SPU)	25 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4066966320145
Customs tariff number	85366990990

**Product Classification**


UNSPSC	39121421
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**


RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**


<b>Compliance Search</b>
Environmental Product Compliance 2002-424/000-006 

**CAD/CAE-Data**

<b>CAD data</b>
2D/3D Models 2002-424/000-006 


**Installation Notes**

**Commoning**



The 1-to-3 adjacent jumper for continuous commoning enables every other terminal block to be commoned. For example, positive and negative potentials can be accommodated alongside each other.

## Commoning



By combining a 1-to-2 continuous jumper with a 1-to-3 adjacent jumper, various commoning applications can be performed in just one jumper slot.