




Een volledig, veelzijdig systeem van modulaire containers, perfect geïntegreerd in de SYSTEM huishoudelijke serie en voldoet aan de installatiebehoeften met hoge bescherming van huishoudelijke, commerciële en industriële sectoren. De 27 COMBI serie is beschikbaar in de versie IP40 en in waterdichte versies met beschermingsgraad IP55, IP65 en IP66, aanbevolen voor alle buitentoepassingen onderhevig aan extreme atmosferische omstandigheden.

|                             |                                         |                             |                               |
|-----------------------------|-----------------------------------------|-----------------------------|-------------------------------|
| Omschrijving                | 6 modules                               | Kleur                       | Grijs RAL 7035                |
| Aant. uitbreekopeningen Ø23 | 8 aan de zijkanten / 2 aan de onderkant | Soort uitbreekopeningen     | Verwijderbaar met gereedschap |
| IP waarde                   | IP40                                    | Isolatie klasse             | II                            |
| Mechanische weerstand       | IK07                                    | Configuratie                | Module 2 x 3                  |
| Compartment voorbereiding   | 3                                       | Kenmerken                   | Halogeenvrij                  |
| Dekselschroeven             | Corrosiebestendig staal                 | Koppel schroeven aandraaien | 0.8 NM                        |
| Buitenste afm. LxHxD (mm)   | 82 x 198 x 55                           | Gloeidraadtest              | 650 °C                        |
| Thermodruk met kogel        | 70 °C                                   | Standaard                   | EN 60670-1                    |
| Installatie temperatuur     | -25 +60 °C                              | Electrocod                  | 0212                          |

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids              |           | Bases        |           | Solvents           |               |               |               | Mineral oil        | UV rays   |
|-----------------|--------------------|-----------|--------------|-----------|--------------------|---------------|---------------|---------------|--------------------|-----------|
|                 | Concentrated       | Diluted   | Concentrated | Diluted   | Hexane             | Benzol        | Acetone       | Alcohol       |                    |           |
| Resistant       | Limited resistance | Resistant | Resistant    | Resistant | Limited resistance | Not resistant | Not resistant | Not resistant | Limited resistance | Resistant |

#### DIMENSIONAL



#### TECHNICAL SYMBOLOGY




IP  
IP40



IK  
IK07



GWT  
650 °C



#### STANDARDS/APPROVALS

