

**VEK-060502: Manifold 1" with "3/4" male threaded outlets for eurocone,, 3/8"-air ven**



**Commercial information**

Messing verdeler 3/4" met ontluuchtingsopening met aantal euroconus aansluitingen

**Basic unit dimensions**

|            |          |
|------------|----------|
| Height     | 58 mm    |
| Length     | 103 mm   |
| Width      | 38 mm    |
| Net weight | 0.529 kg |

**Certificates**

**Applications**

Potable water, Heating, Cooling, Sanitary

**Solutions**

Building installations, Industry, Utility

## Technical characteristics

|                                    |  |                                      |                    |
|------------------------------------|--|--------------------------------------|--------------------|
| Suitable for tap water             | ✓  | Number of branches                   | 2                  |
| Suitable for central heating water | ✓  | Number of branching directions       | 1                  |
| Suitable for cooling water         | ✓  | Distance between offset              | 50 Millimetre      |
| Suitable for compressed air        | ✗  | Max. medium temperature (continuous) | 95 Degrees celsius |
| Suitable for glycol                | ✓  | Width                                | 38 Millimetre      |
| Mounting method                    | Surface mounting                               | Height                               | 58 Millimetre      |
| Model                              | Distributor/collector                          | Length distributor                   | 103 Millimetre     |
| Material                           | Brass  |                                      |                    |
| Surface protection                 | Untreated                                      |                                      |                    |
| Shape                              | Throughflow with straight branches             |                                      |                    |
| Nominal diameter connection 2      | 1 inch (25)                                    |                                      |                    |
| Connection 2                       | Internal thread cylindrical BSPP-G (ISO 228-1) |                                      |                    |
| Nominal diameter branches          | 3/4 inch (20)                                  |                                      |                    |
| Connection branches                | Euroconus standardless                         |                                      |                    |
| Deviant distance between branches  | ✗  |                                      |                    |
| With filling/drain tap             | ✗  |                                      |                    |
| System specific                    | ✓  |                                      |                    |
| With shut-off valve                | ✗  |                                      |                    |
| With de-aeration                   | ✓  |                                      |                    |
| With wall-mounting bracket         | ✗  |                                      |                    |
| With mounting material             | ✗  |                                      |                    |
| With legs                          | ✗  |                                      |                    |
| With insulation                    | ✗  |                                      |                    |
| KOMO certified                     | ✗  |                                      |                    |
| Type approval according to BBR/EKS | ✗  |                                      |                    |