

Bestelnr. 11033



- voor vaste opstelling
- met klapdeksel
- 3 schroefklemmen als verbindingsklem van 1,5 – 2,5 mm²
- andere kleuren op aanvraag

Ampère	16 A
Polen	2 p+PE
Voltage	230 V
Aansluittechniek	schroefklemmen
Contacten	standaard
Beschermingsgraad	IP54
Aanrakingsveiligheid	false
Flens	50x50 mm
Bevestigingsgaten	38x38 mm
Behuizing materiaal	Kunststof
Gewicht	41 g
Certificeringen	EAC, VDE

Technical drawing of the Menekes 230V 16A 2P+N+PE Schuko plug, showing three views with dimensions in mm:

- Front View (Left):** Shows the plug's face with a total width of 61 mm, a central body width of 24 mm, and a mounting bracket width of 38 mm. The central body features the MENEKES logo and two safety symbols: a triangle with a drop and a triangle with a hammer. The mounting bracket has four screw holes with a diameter of $\varnothing 4.5$ mm.
- Side View (Middle):** Shows the plug's profile with a total height of 31 mm, a top flange width of 14 mm, and a base width of 23 mm. The mounting bracket has a height of 21 mm and a base offset of 6.5 mm.
- Top View (Right):** Shows the plug's top with a square mounting bracket measuring 38 mm by 38 mm. The central body has a diameter of $\varnothing 44.5$ mm.

Tekening
1 MB 410

Maten in mm