

VS-ENDCAP: Endcap female for manifold





Commercial information

Female plastic end cap for Henco manifold

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility



Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Max. operating pressure at 20 °C	10 Bar
System specific	✓		
Connection 1	Insert (push-fitting)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	White		
With drain valve	×		
With de-aerator	×		
KIWA certified	×		
Gastec QA	×		
Capped	×		
With connection indicator	×		
FM quality mark	×		
VdS quality mark	×		
UL quality mark	×		
ULC quality mark	×		
LPCB quality mark	×		
DIN-CERTCO certificate	×		
VdS quality mark	×		
With approval for TÜV	×		
DVGW quality mark for gas	×		
DVGW quality mark for water	×		
Compliant with NF 545	×		
KIWA certified	✓		
Gastec QA mark	×		
KOMO certified	×		
Gastec QA - AR 214 (H2)	×		
Type approval according to BBR/EKS	×		

Related products

