


Optix Recessed 600x600 High Output
OPTIX RECESSED 600x600 3L HO 3000K ALU
2023618




PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600x600 3L HO 3000K ALU
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	4450
Luminaire efficacy (lm/W)	124
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768236183

PHOTOMETRY

Optix Recessed 600x600 High Output
OPTIX RECESSED 600x600 3L HO 3000K ALU
2023618



0.5	0.76	E(0°) E(180°)	11422 37.4"
1.0	1.53	E(0°) E(180°)	5868 21"
1.5	2.29	E(0°) E(180°)	3912 15.7"
2.0	3.06	E(0°) E(180°)	2934 11.8"
2.5	3.82	E(0°) E(180°)	2347 9.4"
3.0	4.59	E(0°) E(180°)	1956 7.9"

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle 74.8°)

TECHNICAL DRAWINGS

