

Threefold faceplate, 71 mm centre distance, Niko Intense claystone textured

140-76700



Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Intense. Niko Intense claystone textured



Technical data

Threefold faceplate, 71 mm centre distance, Niko Intense claystone textured.

- Number of spaces for mechanisms: 3
- Colour faceplate: claystone textured
- Colour RAL (approximately): 075 70 10
- Colour NCS (approximately): NCS S 3005-Y50R
- Recommended colour central plate: claystone textured
- Frame composition: It is made of polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Material finishing: polycarbonate (PC) + acrylic-styrene-acrylate (ASA), coated with a textured paint containing polyamide particles with an average grain size of $40 \pm 1 \mu\text{m}$
- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: coated claystone textured
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Minimum ambient temperature: -5°C
- Maximum ambient temperature: 40°C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 85 mm x 225 mm x 8.9 mm