HENSEL



MV FP 66

IP 55

• Kabelinvoerflens

VERBINDINGSGEGEVENS

MECHANISCHE EIGENSCHAPPEN

IP-beschermingsklasse:	IP55
Afdichting van de kabelinvoer:	30 mm - 72 mm
Geeignet für Wandstärke:	Minstens 1.5 mm

MILIEUOMSTANDIGHEDEN

Toepassingsgebied:	Binnen of beschermde buiten opstelling
Maximale omgevingstemperatuur 24u:	35 °C
Omgevingstemperatuur:	-25 °C tot +40 °C
Relatieve vochtigheid:	≤ 50 % bij 40 °C, ≤ 100 % bij 25 °C

MATERIAALEIGENSCHAPPEN

materiaal:	TPE
Gloeidraadtest volgens IEC 60695-2-11:	750 °C
Temperatuurbestendigheid:	-25 °C tot +100 °C
Halogeenvrij:	Ja
siliconenvrij:	Ja

AFMETINGEN

Hoogte:	100 mm
Breedte:	248 mm
Diepte:	160 mm
Nettogewicht:	0.427 kg

Gustav Hensel GmbH & Co. KG * Gustav-Hensel-Str. 6 * 57368 Lennestadt * Deutschland * Telefon: +49 (0)2723/609-0

DISTRIBUTIEGEGEVENS

Productnummer:	6600249
EAN:	4012591692492
verpakkingseenheid:	1
Douanetariefnummer:	85371098
ETIM klasse:	DYNAMIC: EC000211 - Gland plate for enclosure/cabinet ETIM-8.0: EC000211 - Gland plate for enclosure/cabinet ETIM-7.0: EC000211 - Gland plate for enclosure/cabinet ETIM-6.0: EC000211 - Gland plate for enclosure/cabinet ETIM-5.0: EC000211 - Gland plate for enclosure/cabinet ETIM-4.0: EC000211 - Gland plate for enclosure/cabinet

TEKENINGEN

