



### Features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 2800lm; 25W; 112lm/W; 4000K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1200mm x 89mm x 88mm; D-mark; 3-hour LiFePO4 maintained emergency batteries (600lm emergency lm output) with DALI interface.

### Product Overview

<b>Product name</b>	RESISTO 1200 IP66 2800LM 840 EM PRO
<b>Technology</b>	LED
<b>Cap/Base</b>	N/A
<b>Housing</b>	PC Polycarbonate
<b>Mount</b>	Ceiling surface mounting, Suspended, Wall surface mounted
<b>General application</b>	Logistics & Industry
<b>ETIM Class</b>	EC002892
<b>Fixture luminous flux (lm)</b>	2800
<b>Luminaire efficacy (lm/W)</b>	112
<b>Correlated colour temperature (k)</b>	4000
<b>Light colour</b>	Neutral White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	5
<b>Beam Angle (°)</b>	110
<b>Glare control</b>	< 22
<b>Photobiological Risk Group</b>	RG1
<b>Luminous flux (emergency) (lm)</b>	600

