

### Features

- 400mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct/indirect (halo) light distribution, 1715lm luminous flux, 16W system power, 107lm/W luminaire efficacy. DALI dimmable. 3 hours integrated emergency. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR≤19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.


### Product Overview

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Product name                    | COLOSSAL 400mm 940 PRISM DIR+HAL WHITE DALI EM |
| Technology                      | LED (3 SDCM)                                   |
| Cap/Base                        | N/A                                            |
| Housing                         | Aluminium                                      |
| Mount                           | Suspended                                      |
| Fixture luminous flux (lm)      | 1715                                           |
| Luminaire efficacy (lm/W)       | 102                                            |
| Colour temperature (K)          | 4000                                           |
| Light colour                    | Neutral White                                  |
| CRI (Ra)                        | 90                                             |
| Colour Variation Initial (SDCM) | 3                                              |
| Glare control                   | < 19                                           |
| Photobiological Risk Group      | RG0                                            |
| Total power consumption (W)     | 16.9                                           |
| Electrical protection           | Class I                                        |
| Control gear type               | LED driver constant current                    |
| LED Flickering Rate             | Ultra low (5% or less)                         |


COLOSSAL 400mm 940 PRISM DIR+HAL WHITE DALI EM  
2071159

|                    |                                  |
|--------------------|----------------------------------|
| Housing colour     | RAL 9016 - Traffic white / Bezel |
| IP rating          | IP40/20                          |
| IK rating          | IK07                             |
| Product EAN number | 5025768711598                    |
| Warranty           | 5 years                          |
| Colour Code        | 940                              |

Photometry



Technical drawings



### Data table

#### GENERAL DATA

|                                  |                                                |
|----------------------------------|------------------------------------------------|
| Product name                     | COLOSSAL 400mm 940 PRISM DIR+HAL WHITE DALI EM |
| Technology                       | LED (3 SDCM)                                   |
| Cap/Base                         | N/A                                            |
| Housing                          | Aluminium                                      |
| Mount                            | Suspended                                      |
| Operating temperature range (°C) | 10°C...+25°C                                   |
| Warranty                         | 5 years                                        |

#### OPTICAL DATA

|                                 |               |
|---------------------------------|---------------|
| Fixture luminous flux (lm)      | 1715          |
| Luminaire efficacy (lm/W)       | 102           |
| Colour temperature (K)          | 4000          |
| Colour Code                     | 940           |
| Light colour                    | Neutral White |
| CRI (Ra)                        | 90            |
| Colour Variation Initial (SDCM) | 3             |
| Glare control                   | < 19          |
| Photobiological Risk Group      | RG0           |
| Emergency duration (h)          | 3             |

#### ELECTRICAL DATA

|                                          |                             |
|------------------------------------------|-----------------------------|
| Total power consumption (W)              | 16.9                        |
| Primary Supply/Product voltage - min (V) | 220                         |
| Lamp power factor                        | 0.95                        |
| Electrical protection                    | Class I                     |
| Control gear required                    | No                          |
| Control gear type                        | LED driver constant current |
| Drive current (mA)                       | 350                         |
| Inrush Current (A)                       | 20                          |

## COLOSSAL 400mm 940 PRISM DIR+HAL WHITE DALI EM 2071159

|                                                          |                        |
|----------------------------------------------------------|------------------------|
| Inrush Duration (µs)                                     | 200                    |
| Glow Wire Test (°C)                                      | 650                    |
| Energy Efficiency Class (A->G) of contained light source | C                      |
| Nominal Frequency (Hz)                                   | 50/60Hz                |
| LED Flickering Rate                                      | Ultra low (5% or less) |
| Max. products per 10A C Breaker                          | 31                     |
| Max. products per 20A B Breaker                          | 37                     |
| Connectable conductor cross section - Min (mm²)          | 1.5                    |
| Connectable conductor cross section - Max (mm²)          | 2.5                    |

### LIFETIME DATA

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 170000 |
| Lifespan L80 B20 | 145000 |
| Lifespan L90 B10 | 66000  |

### PHYSICAL DATA

|                               |                                  |
|-------------------------------|----------------------------------|
| Housing colour                | RAL 9016 - Traffic white / Bezel |
| IP rating                     | IP40/20                          |
| IK rating                     | IK07                             |
| Diffuser finish               | Prismatic                        |
| Diffuser material             | PMMA Acrylic                     |
| Nominal Product Diameter (mm) | 400                              |
| Weight (kg)                   | 6.8                              |

### PACKAGING

|                                      |                |
|--------------------------------------|----------------|
| Single packaging type                | Carton         |
| Product EAN number                   | 5025768711598  |
| Packaging single width (cm)          | 47.0           |
| Packaging single depth (cm)          | 47.0           |
| DUN14 (outer)                        | 05025768711598 |
| Packaging outer length / height (cm) | 14.0           |

# Concord

COLOSSAL 400mm 940 PRISM DIR+HAL WHITE DALI EM  
2071159

### SAFETY DATA

|                                     |       |
|-------------------------------------|-------|
| Optimal operating condition (°C)    | 10-25 |
| Special purpose lamp                | No    |
| Dry applications use only           | No    |
| Suitable for household illumination | No    |