


VB050502-BLAUW: Manifold 3/4" with ball valves - 2 EK-conections Blue



Commercial information

Messing Henco verdeler 3/4" aansluiting met bolkraan en euroconus aansluitingen

- Universele euroconus-aansluitingen
- Per groep afsluitbaar
- Korte inbouwlengthe
- Kan zowel horizontaal als verticaal als ondersteboven geïnstalleerd worden

Beschikbaar in een 3/4" en een 1" uitvoering

Beschikbaar in blauw en rood.

Geschikt voor verwarming, air conditioning en sanitaire installaties.

Via configuratie verdeler mogelijkheid tot parallel gebruik van koude en/of warme circuits.

Basic unit dimensions

Height	70 mm
Length	105 mm
Width	50 mm
Net weight	0.365 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	2
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	50 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	50 Millimetre
Mounting method	Surface mounting	Height	70 Millimetre
Model	Distributor/collector	Length distributor	105 Millimetre
Material	Brass		
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	3/4 inch (20)		
Connection branches	Euroconus standardless		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✓		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		