



# Connected motor control, base, 3 A, 71 x 71 mm, screw fixing, Zigbee®

## 552-72311

 3 A  
250 Vac



The connected Zigbee® motor control contains a switching contact to control a 230 V motor. It contains a transmitter and receiver that communicate wirelessly with the wireless smart hub for Niko Home Control (552-00001).

You can use the connected motor control to replace a conventional motor control. The connected motor control can switch its own contacts.

With the addition of the wireless smart hub for Niko Home Control (552-00001), it is possible to configure additional functionalities with the Niko Home Control programming software. For example, it becomes possible to add it to a scene or all-off function. This device can also be used in a bus wiring installation in combination with the wireless bridge for Niko Home Control (550-00640).

This article is protected by at least one patent (or patent application). For more info on patents, see [www.niko.eu/innovation](http://www.niko.eu/innovation).



## Technical data

Connected motor control, base, 3 A, 71 x 71 mm, screw fixing, Zigbee®.

- max. load per channel: 10 A
- modification of settings: Niko Home Control programming software or Niko Home App (requires smart hub)
- maximum load: 3 A
- maximum range (from switch to smart hub): 10 m
- Maximum number per installation: 50 connected Zigbee® devices
- Compatible with the wireless bridge
- Function: motor control
- Type of control: push button
- Number of buttons: 2
- Led colour: white
- Number of leds: 2
- Maximum MCB rating: 16 A (limited by national installation rules)
- Wireless communication protocol: Zigbee® 3.0
- System compatibility: talks with Homey (Zigbee®)
- Protection degree: IP20
- Minimum flush-mounting depth: 40 mm
- Required type of flush-mounting box:

- depth: min. 40 mm (cabling space included)
- claw/screw fixing: 60 mm
- inner diameter box: 60 mm
- multiple boxes centre distance horizontal: 71 mm
- multiple boxes centre distance vertical: 71 mm
- multiple boxes centre distance vertical: 60 mm for Belgium and France
- Type of fastening:
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Centre-to-centre distance:
  - horizontal coupling and vertical coupling with centre-to-centre distance 71 mm
  - horizontal connection of several bases is quick and perfect thanks to the folded-up dovetails on the left and right side
  - extra robustness due to the folded-up edges on the outside of the base and the continuation to the inside of the base
- Terminals wire capacity: 2 x 2.5 mm<sup>2</sup>
- Suitable type of wire: rigid (solid or stranded)
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 73 mm x 73 mm x 38.6 mm
- Certification marks: Zigbee Certified Product
- Marking: CE

## Dimensions

