



De verdeelkasten voor bouwplaatsen type Q-BOX zijn ontworpen om de effecten van slijtage, impact en druk veroorzaakt door de atmosfeer te weerstaan. Ze zijn verkrijgbaar in bedrade versies voorzien van vergrendelde contactdozen (met of zonder zekeringhouder) tot 63 A, of contactdozen type IEC 309. De bedrade versies zijn ook voorzien van accessoires zoals de nooddrukknoop, afsluitbare deuren, roestvrij stalen, scheurbestendige kabelbevestigingshaken en ingebouwde transporthandvatten op het bovenste deel van de kast. Om de best mogelijke positionering op de bouwplaats te garanderen, kunnen 68 Q-BOX ACS-kasten worden opgebouwd, aan de vloer worden bevestigd of op polen.

Type	Q-BOX 6 ACS	type bord	Bedraad
Kleur	Lichtblauw	Buitenste afm. LxHxD (mm)	914x821x400
Gewicht (kg)	31	In overeenstemming met normen	EN 61439-4 (ACS)
Kenmerken	UV-bestendigheid (EN 62208)	IP waarde	IP55
Mechanische weerstand	IK10	Gloeidraadtest	650 °C
Thermodruk met kogel	70 °C	Isolatie klasse	II
Voeding	Klemmenblok	Aant. polen	3P+N+E
Leverbaar vermogen (kW)	17	Hoofd schakelaar	RCBO 32 A 4P 6 kA 0,03 A - AC-type
Kortsluitingsbeveiliging	Zekering	Aant. contactdozen	6
Wandcontactdoos 2P+E 16 A - IB	3	Wandcontactdoos 3P+E 16 A - IB	3
Nooddrukknoop	Ja		

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	Limited resistance	Limited resistance	Limited resistance	Resistant	Limited resistance	Resistant

#### DIMENSIONAL



#### TECHNICAL SYMBOLOGY



EN 61439-4 (ACS)



UV-bestendigheid (EN 62208)

**IP**

IP55

**IK**

IK10

**GWT**

650 °C



70 °C



II

#### STANDARDS/APPROVALS



GEWISS S.p.A. Via Domenico Bosatelli 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 10/03/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice