

Double socket outlet with side earthing and shutters, ultra flat, vertical, white

101-67835

4 year warranty

Technical data

Double socket outlet with side earthing and shutters, ultra flat, vertical, white

- Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
- Type of earthing: side earthing
- Power: 16 A/250 Vac
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides
 - with 2 grooves
- Required type of flush-mounting box
 - Oval shaped flush-mounting box: Attema UK40/PVK40 or ABB Haf H140
 - claw/screw fixing: 60 mm
 - inner diameter box: 60 mm
 - multiple boxes centre distance horizontal: 71 mm
 - multiple boxes centre distance vertical: 71 mm
 - multiple boxes centre distance vertical: 60 mm for Belgium and France
- Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is coloured in mass.
- Material earthing: side earthing in high quality brass
- Fixing method
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires
- Wire capacity
 - 2 x 2.5 mm² per connection terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Protection degree: IP20-D
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20-D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: KEMA, SEMKO, DEMKO, VDE
- Marking: CE



$\frac{16 A}{250 Vac}$ CE

niko

Wiring diagram

