


# Optix Surface 1200 Direct - Indirect High Output

OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU DALI  
2023745



## Product features

- OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU DALI is a high efficacy low glare luminaire for office and education applications. Direct / Indirect lighting with 80% downlight and 20% uplight ratio for ceiling suspended mounting. Size: 1129x200x45mm. Aluminised plastic extra low glare optics in 2 lines configuration. White RAL9016 fixture body. DALI dimmable. 4000K Neutral White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 5600lm. Power consumption 34W. Luminaire efficacy 165lm/W. Lifespan: 60,000 hours L90B10. UGR<16, Luminance at 65°<200 Cd/m<sup>2</sup>, IK07, IP20. Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C.




## PRODUCT OVERVIEW

|                                   |   |
|-----------------------------------|---|
| Product name                      | OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU DALI |
| Technology                        | LED (3 SDCM)  |
| Cap/Base                          | N/A   |
| Housing                           | Steel   |
| Mount                             | Suspended   |
| Fixture rating                    | Enclosed  |
| General application               | Education, Office                                   |
| ETIM Class                        | EC002892  |
| Warranty                          | 5 years   |
| Useful luminous flux (Fuse)       | 5600  |
| Fixture luminous flux (lm)        | 5600  |
| Luminous flux (lm)                | 5600  |
| Luminaire efficacy (lm/W)         | 165   |
| Correlated colour temperature (k) | 4000  |
| Light colour                      | Neutral White                                       |
| CRI (Ra)                          | 80  |
| Colour Variation Initial (SDCM)   | SDCM3   |
| Glare control                     | < 16  |
| Photobiological Risk Group        | RG1   |
| Total power consumption (W)       | 34  |
| Electrical protection             | Class I   |
| Control gear type                 | LED driver constant current                         |
| Dimmable                          | Yes   |
| Dimming method                    | DALI  |
| LED Flickering Rate               | Ultra low (5% or less)                              |
| Housing colour                    | RAL 9016 - Traffic white / Bezel                    |
| IP rating                         | IP20  |
| IK rating                         | IK07  |
| Product EAN number                | 5025768237456                                       |

## Optix Surface 1200 Direct - Indirect High Output

*OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU DALI*  
2023745

### PHOTOMETRY



### TECHNICAL DRAWINGS

