

Optix Surface 1200 Direct Medium Output SylSmart
OPTIX SURFACE 1200 2L LUMI 4K ALU SSC
2023829



Product features

- OPTIX SURFACE 1200 2L LUMI 4000K ALU SSC is a surface mounted luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. SylSmart Standalone enabled. 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 4000K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.782; Fidelity Index R : 93; Gamut Index R : 98. For 4000K luminous flux: 3800lm. Power consumption: 37W. Luminaire efficacy: 103lm/W. UGR<16 Luminance at 65°<200 Cd/m2, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 60,000hrs L80B20 lifespan.




PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200 2L LUMI 4K ALU SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3810
Fixture luminous flux (lm)	3810
Luminous flux (lm)	3810
Luminaire efficacy (lm/W)	103
Light colour	Neutral White
CRI (Ra)	98
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG0
Total power consumption (W)	37
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSC
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238293

PHOTOMETRY

Optix Surface 1200 Direct Medium Output SylSmart
OPTIX SURFACE 1200 2L LUMI 4K ALU SSC
2023829



TECHNICAL DRAWINGS

