## Double socket outlet with side earthing and shutters, vertical, white

## 101-67865



## **Technical data**

Double socket outlet with side earthing and shutters, vertical, white

- Colour: white (coloured in mass, approximately NCS S 0502 Y50R, RAL 9010)
- Type of earthing: side earthing
- Flush-mounting frame
  - 1 mm-thick metal
  - galvanized on all sides
  - with 2 grooves
- · Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is coloured in mass.
- Material earthing: side earthing in high quality brass
- · Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- - contact buses fitted with plug-in terminals for clamping the wires
- · Wire capacity
  - $-2 \times 2.5 \text{ mm}^2$  per connection terminal
- · Earthing wire capacity
  - $-2 \times 2.5 \text{ mm}^2 + 2 \times 4 \text{ mm}^2$  wire in the earthing terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Dimensions (HxWxD): 106.8 x 81 x 63 mm
- Certification marks: KEMA, SEMKO, DEMKO, VDE
- Marking: CE







## Wiring diagram

