

## Product data sheet

Item No. 96.021.0253.0

### Female connector with strain relief RST20I2F B23ZRX GL

Splitter connector with RST20I2, 2 pole, double strain relief (feed through wiring), female, spring clamp connection, 250V/20A, forcable diameters 6-10mm, color of coding: light gray, color of housing: light gray



Item No.	96.021.0253.0
EAN	4015573907904
Order Unit	100 Piece(s)

### Certificates / Approvals



### Technical data

#### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	

#### Connection Data

Cable diameter	6 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Connection cross section stranded	1.5 mm <sup>2</sup>
Terminations per pole	2

#### Model

Model	female
-------	--------

Number of poles	2
Connection type	Tension clamp connection
Degree of protection (IP)	IP66/IP68
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve

## Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

## Dimensions

Length	96 mm
Width	59 mm
Height	38 mm

## Technical drawing

